

MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION:

PRODUCT CODE N0038

PRODUCT NAMENAT. ETHYL ACETATE

SUPPLIER Shanghai M & U International Trade Co., Ltd.

Rm 1717, No 598 North NuJiang Road

200333 Shanghai, China +86-21-32515501 32515502

sales@mu-intel.com

FOR EMERGENCIES CALL CHEMTREC: 800-424-9300 (24-HOURS)

2. HAZARD IDENTIFICATION:

Emergency Overview

OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

Target Organs

Blood, Kidney, Liver, Central nervous system

GHS Classification

Flammable liquids (Category 2)

Acute toxicity, Inhalation (Category 5)

Eye irritation (Category 2A)

Specific target organ toxicity - single exposure (Category 3)

GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation. H333 May be harmful if inhaled.

H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P305 P351 P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Other hazards

Repeated exposure may cause skin dryness or cracking.

HMIS Classification

Health hazard 2

Flammability 3 Physical hazards 2

NFPA Rating

Health hazard 2
Fire 3
Reactivity Hazard 0
Potential Health Effects

Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Vapors may

cause drowsiness and dizziness.

Skin May be harmful if absorbed through skin. Causes skin irritation.

Eyes Causes eye irritation.

Ingestion May be harmful if swallowed.

3. COMPOSITION AND INFORMATION ON INGREDIENTS:

Formula C4 H8 O2 **Molecular Weight** 88.11 g/mol

CAS-No EC-No Index-No. Registration number

141-78-6 205-500-4 607-022-00-5 01-2119475103-46-XXXX

4. FIRST-AID GUIDE:

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIRE-FIGHTING GUIDE:

Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE GUIDE:

Personal precautions

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13).

7. HANDLING AND STORAGE:

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE AND PERSONAL PROTECTION:

Personal protective equipment:

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance

Form LIQUID

Color COLORLESS TO PALE YELLOW

Safety data

pH no data available

Melting point (°C) <83
Boiling point (°C) 78
Flash point (°F) Closed cup 24
Ignition temperature (°C) 427
Lower explosion limit 2.29

Lower explosion limit 2.2 %(V) Upper explosion limit 11.5 %(V) Vapor pressure (mm Hg @20 °C) 99

Density @25 °C 0.895

Water solubility MODERATE

Partition coefficient:

n-octanol/water log Pow: 0.73

Relative vapor density 3.0

Odor SWEET, ESTER

10. STABILITY AND REACTIVITY:

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapors may form explosive mixture with air.

Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Materials to avoid

Strong oxidizing agents

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

11. TOXICOLOGICAL INFORMATION:

Acute toxicity

Oral LD50

LD50 Oral - rat - 5,620 mg/kg

Inhalation LC50.

LC50 Inhalation - mouse - 2 h - 45,000 mg/m3

Dermal LD50

LD50 Dermal - rabbit - > 180,000 mg/kg

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC:

No component of this product present at levels greater than or equal to 0.1% is identified as probable. possible or confirmed human carcinogen by IARC.

ACGIH:

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP:

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA:

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Specific target organ toxicity - single exposure (Globally Harmonized System)

May cause drowsiness or dizziness.

Potential health effects

Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Vapors

may cause drowsiness and dizziness.

Ingestion May be harmful if swallowed.

Skin May be harmful if absorbed through skin. May cause skin irritation.

Eyes Causes eye irritation.

Signs and Symptoms of Exposure

Central nervous system depression, Drowsiness, narcosis, anemia.

Additional Information RTECS: AH5425000

12. ECOLOGICAL INFORMATION

Toxicity

Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 350.00 - 600.00 mg/l - 96h

LC50-Pimephales promelas (fathead minnow) - 220.00 - 250.00 mg/l -96h

Toxicity to daphnia

ia EC50 - Daphnia magna (Water flea) - 2,300.00 - 3,090.00 mg/l - 24 h

and other aquatic

invertebrates LC50 - Daphnia magna (Water flea) - 560 mg/l - 48 h

Toxicity to algae EC50 - Algae - 4,300.00 mg/l - 24 h

EC50 - SELENASTRUM - 1,800.00 - 3,200.00 mg/l - 72 h

13. DISPOSAL RECOMMENDATIONS:

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a

licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORTATION INFORMATION:

DOT (US)

UN number: 1173 Class: 3 Packing group: II Proper shipping name: ETHYL ACETATE

IMDG

UN number: 1173 Class: 3 Packing group: II Proper shipping name: ETHYL ACETATE

IATA

UN number: 1173 Class: 3 Packing group: II Proper shipping name: ETHYL ACETATE

15. REGULATORY INFORMATION:

OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Ethyl acetate CAS-No. Revision Date

141-78-6 2007-03-01

Pennsylvania Right To Know Components

Ethyl acetate CAS-No. Revision Date

141-78-6 2007-03-01

New Jersey Right To Know Components

Ethyl acetate CAS-No. Revision Date

141-78-6 2007-03-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION:

The information in this MSDS was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy.

Since the conditions for use, handling, storage and disposal of this product are beyond M&U's control, it is the responsibility of the user both to determine safe conditions for use of this product and to assume liability for loss, damage, or expense arising out of the products improper use. No warranty expressed or implied regarding the product described herein will be created by or inferred from any statement or omission in the MSDS. Various federal, state, or provincial agencies may have specific regulations concerning the transportation, handling, storage, use, or disposal of this product which may not be reflected in the MSDS. The user should review these regulations to ensure full compliance.

